


#10

DIN 1897 N
 (ГОСТ 4010)

Extra kurze Spiralbohrer mit Zylinderschaft

Zum Bohren von Kohlenstoffstahl, legiertem Stahl, Konstruktionsstahl und Grauguss



| d mm | L mm | l mm |
|-----------|---------|---------|
| 0,50-0,52 | 20 | 3 |
| 0,55-0,60 | 21 | 3.5 |
| 0,62-0,65 | 22 | 4 |
| 0,68-0,75 | 23 | 4.5 |
| 0,78-0,85 | 24 | 5 |
| 0,88-0,95 | 25 | 5.5 |
| 0,98-1,05 | 26 | 6 |
| 1,10-1,15 | 28 | 7 |
| 1,19-1,30 | 30 | 8 |
| 1,35-1,50 | 32 | 9 |
| 1,55-1,70 | 34 | 10 |
| 1,75-1,90 | 36 | 11 |
| 1,95-2,10 | 38 | 12 |
| 2,15-2,35 | 40 | 13 |
| 2,38-2,65 | 43 | 14 |
| 2,70-3,00 | 46 | 16 |
| 3,10-3,35 | 49 | 18 |
| 3,40-3,70 | 52 | 20 |

| d mm | L mm | l mm |
|-------------|---------|---------|
| 3,80-4,25 | 55 | 22 |
| 4,30-4,70 | 58 | 24 |
| 4,76-5,30 | 62 | 26 |
| 5,40-6,00 | 66 | 28 |
| 6,10-6,70 | 70 | 31 |
| 6,75-7,50 | 74 | 34 |
| 7,54-8,50 | 79 | 37 |
| 8,60-9,50 | 84 | 40 |
| 9,52-10,60 | 89 | 43 |
| 10,70-11,80 | 95 | 47 |
| 10,90-13,20 | 102 | 51 |
| 13,30-14,00 | 107 | 54 |
| 14,25-15,00 | 111 | 56 |
| 15,08-16,00 | 115 | 58 |
| 16,25-16,75 | 119 | 60 |
| 17,00-18,00 | 123 | 62 |
| 18,25-19,00 | 127 | 64 |
| 19,05-20,00 | 131 | 66 |